

SCT71405A00STER



SCT71405FxxOWCR

NAME	PIN	
	ESOP-8	ESOP-8

NAME	PIN FUNCTION		
	TO252-4	TO252-4	
	1		

1

PARAMETER（4-layer）

SYMBOL	PARAMETER	TEST CONDITION	MIN	TYP	MAX	UNIT
Power Supply						
	( ) ( )					


Iq/uA
Iload/mA


Iq/uA
VIN/V


Current Limit/mA
Temperature/




VOUT/V
Iload/mA


Isd/uA
2
1.8
1.6
1.4
1.2
1
0.8
0.6
0.4
0.2
0
-40 -25 -10 5 20 35 50 65 80 95 110 125
Temperature/

Iq/uA
Temperature/


Current Limit/mA
Temperature/


Frequency (Hz)




Frequency (Hz)




Frequency (Hz)


VIN
VIN
Thermal Shutdown
& Current Limit
VIN UVLO
Regulator

Overview

Over Current Limit and Foldback Current Limit



Power-Good and Power-Good Delay

Typical application 1:



Output Voltage

Table 1: Compensation Values for Typical Output Voltage/Capacitor Combinations

Power Dissipation and Thermal Performance

Application Waveforms









Application Waveforms(Continued)













Layout Guideline

1.
2.


3.05
3.23
4.70
5.10
5.80
2.16
2.35
3.80
4.20
SEATING PLANE
0.00
0.25
0.33
BSC
SIDE VIEW
FRONT VIEW
0.60
1.27
1.40
TYP
2.36
TYP
5.50
TYP
0.25 BSC
0.40
1.27
3.25
DETAIL "A"

NOTE:

1.
2.
3.
4.
5.
6.