

4.2V-60V Vin, 2A, High Efficiency Step-down DCDC Converter with Programmable Frequency

FEATURES

- 82,0 %
- 0 A
- 0,6 /
- 00.
- A
- 8/.
- &
- /.
- 2
- +
- /.
- /,0
- A
- +
- &
- +
- +
- +6

APPLICATIONS

-

REVISION HISTORY

8

,

	4	
	5	
	6	, A
	7	A , , ,

RECOMMENDED OPERATING CONDITIONS

		2,0	4.	
		. ,6	35	
		+2.	/3.	A

ESD RATINGS

	* & * + A+ ± . /+0. /2	+0	) 0	
	A 0. /2 * &A * + A+ ± . 0+	± ,3	) . ,3	
(1) A /33 3. . ,				
(2) A /35 03. A ,				

THERMAL INFORMATION


8/ 80		15,17	A-
80	+ +	5,/ 4	
80	+ +	/ 4,22	
A 8/ 80		5/ ,55	
80	+ +	/ 4,70	
8/ A	A *	, A	
8 A	A 0400	*	*
		A 0400, A	, A A
		A,	
80	3/ +5*2+ A ,		
	,	3/ +5	A
,		,	

ELECTRICAL CHARACTERISTICS

02 * +2. A /03 A*	03 A,		

			1,3	
			2. .	
		. *	0 3	
		* * * + * + 3 *	/ . .	
		0. .		
	+ +	+ 3	00.	
			. ,570 . ,6 . ,6. 6	

TYPICAL CHARACTERISTICS




0, A * 3 1, A * 02


2, * 02 * 1,1 3, A

4, 5,

FUNCTIONAL BLOCK DIAGRAM




6,



&

&



7,

A 0400

. ,6 ±/

, /

*

,

1

,

*

*

—

&

•

,

•

,

A 0400

-A

*

,

*

-A

/ . .

/ ,0

,

-A

2


. ,3

/ . ,

-A

,

—



*

/ . ,
A

*

-A

/ . .

/ ,0

44

-A

0

*

. ,2

*

6.

,

-A

*

/ . ,

*

*

,

63 ,

,

8 A
8
8
8

Table 1. R_5 , R_6 Value for Common Output Voltage (Room Temperature)

0,3	0/,3	/ . ,0
1,1	1/,4	/ . ,0
3	31,4	/ . ,0
/0	/21	/ . ,0
02	072	/ . ,0
14	220	/ . ,0
26	4. 2	/ . ,0

Table 2. R_{FSW} Value for Common Switching Frequencies (Room Temperature)

+ +

/ . ,

& .

•
•
•
•
•

+ +

+

*

//

,

â Ç•6Sô"Ü"y5

& /

•
•
•
•
•
•

&
&

9 íă 9 •íă

A
/ 0

*

,

,

*

*

4. +

A 0400,

* 14. $+ / 1 +$

14. $+1+ \dots, 5 \quad 1 \dots$

$$\begin{array}{c} + \\ * \end{array}$$

+

+

12

14. $+ / 1 +$

0. . ,

 12^*

. , 44 ,

8/2

A

$$+A$$

+

A A

A A

3

5

*

A

& , ,

• , /

& 4. 1

/3,

& 3

0(* 8

8/4

A

/5

3.

8/5

02 * 1,1 *

